

ABS DEE

Drain, Waste & Vent

FITTINGS

Specification sheet



An Orbia business.

Overview

BOW ABS drain, waste and vent (DWV) fittings are manufactured to ASTM D2661. Basic use is for plumbing DWV and storm drainage applications.

The fittings are solvent weld to ABS pipe made to ASTM F628, ASTM D2661 and CSA B181.1.

Solvent cement must comply with ASTM D2235.

Laying lengths of the fittings meet the requirements of ASTM D3311.

Standards

ASTM D2661

Listings

Listing holder: Bow Plumbing Group Inc.

NSF 14

cNSF@us dwv

NSF@dwv

Technical Data

Material:

ABS cell classification 32222 as specified in ASTM D3965



August 2025



Orbia's Building and Infrastructure business Wavin is an innovative solutions provider for the global building and infrastructure industry. Backed by more than 60 years of product development experience, Wavin is advancing life around the world by building healthy, sustainable environments for global citizens. Whether it's to improve the distribution of clean drinking water, to make sanitation accessible for everyone, to create climate resilient cities, or to design comfortable living spaces, Wavin collaborates with municipal leaders, engineers, contractors, and installers to help future-proof communities, buildings and homes. Wavin has 12,000+ employees around 65 production sites worldwide, serving over 80 countries through a global sales and distribution network.

Wavin 950 Winter Street, South Entrance 1st Floor, Waltham, MA 02451, United States | 5700 Côte de Liesse Montréal, QC H4T 1B1
Phone CAN 514-735-7585 / 1800-561-1169 | US 514-735-3632 / 1800-763-3632 | E-mail wavin.northamerica@wavin.com | wavin.us

© 2025 **Wavin** Wavin reserves the right to make alterations without prior notice. Due to continuous product development, changes in technical specifications may change. Installation must comply with the installation instructions.

