

SuperPex

Polyalloy Insert Fittings for Pex Tubing

Specification Sheet



BOW Groupe
de Plomberie Inc.

Overview

The intended use of the product is for installation in hot and cold potable water distribution systems, as well as hydronic radiant heating systems using SDR 9 tubing manufactured against ASTM F876 or CSA B137.5.

For potable hot and cold water distribution, use the Superpex polyalloy insert fittings with tubing designed for potable water distribution such as Superpex. For hydronic radiant heating and cooling, use the Superpex polyalloy insert fittings with tubing manufactured with an oxygen barrier tubing such as Oxpex. The Superpex polyalloy insert fittings exhibit excellent corrosion resistance and are a superior alternative to metal fittings.

Technical Data

Material:

Polyphenylsulfone blend or Polysulfone meeting the requirements of ASTM D6394 as required by ASTM F2159.

Continuous working pressure:

690 kPa - 82°C / 100 psi @ 180°F

1103 kPa - 23°C / 160 psi @ 73°F

Standards

Made to the dimensional, material and performance requirements of ASTM F2159, ASTM F877 and CSA B137.5

Listings

Listing holder: Bow Plumbing Group Inc.

NSF 14; NSF 61; cNSFus-pw

CSA B137.5; ASTM F2159

Precautions

Bow Superpex Polyalloy Insert Fittings

- Should not be painted
- Should not be exposed to cleaners, chemicals, solvents or glues
- Should always be stored in clean, preferably lined bins or containers
- Cannot be used in compressed air systems
- Should not be installed in concrete or under a slab
- Shall be joined by copper crimp rings meeting the requirements of ASTM F1807
- Bow Superpex polyalloy insert fittings with male pipe threads must only use PTFE tape as a thread sealant
- Should not be exposed to direct ultra violet light
- Do not use soap or detergent solutions for leak detection



August 2025

Orbia's Building and Infrastructure business Wavin is an innovative solutions provider for the global building and infrastructure industry. Backed by more than 60 years of product development experience, Wavin is advancing life around the world by building healthy, sustainable environments for global citizens. Whether it's to improve the distribution of clean drinking water, to make sanitation accessible for everyone, to create climate resilient cities, or to design comfortable living spaces, Wavin collaborates with municipal leaders, engineers, contractors, and installers to help future-proof communities, buildings and homes. Wavin has 12,000+ employees around 65 production sites worldwide, serving over 80 countries through a global sales and distribution network.

Wavin 950 Winter Street, South Entrance 1st Floor, Waltham, MA 02451, United States | 5700 Côte de Liesse Montréal, QC H4T 1B1
Phone CAN 514-735-7585 / 1800-561-1169 | US 514-735-3632 / 1800-763-3632 | E-mail customer.service@orbia.com | wavin.us | wavin.ca

© 2025 Wavin Wavin reserves the right to make alterations without prior notice. Due to continuous product development, changes in technical specifications may change. Installation must comply with the installation instructions.