

SuperPEX

PEX Potable Water Pipe



BOW Groupe
de Plomberie Inc.

Overview

SuperPEX tubing is manufactured for use in hot and cold potable water distribution including industrial, commercial, high-rise and multi-family residential facilities.

- Is made in 3/8", 1/2", 3/4" and 1" nominal sizes.
- Available in coils and in straight lengths.
- The tubing is made to CTS (Copper Tube Size) outside dimensions and an SDR (Standard Dimension Ratio) of 9.
- SuperPEX tubing can also be used as a water service pipe buried underground outside of a building.

Technical Data

Material:

Crosslinked polyethylene,
PEX Silane Method (PEX-b), PEX 5306

Continuous working pressure:

690 kPa - 82°C / 100 psi @ 180°F
1100 kPa - 23°C / 160 psi @ 73°F

Chlorinated Potable Water:

550 kPa - 60°C / 80 psi @ 140°F

Caution: do not use when chlorine dioxide is present in the water treatment systems as it might significantly reduce product lifetime.

Standards

CSA B137.5; ASTM F877; ASTM F877; AWWA C904

Compatible fittings:

ASTM F1807; ASTM F2159

SmartCoil™

SmartCoil packaging allows you to pull the desired length of the pipe while keeping the rest wound and wrapped for future use!



Listings

Listee holder: Bow Plumbing Group Inc.

NSF 14; NSF 61; cNSF[®]us pw; CSA B137.5; ASTM F876; ASTM F877; HUD (MR1293g); AWWA C904.

The tubing also has listings with:

- ULC to CAN/ULC S101, design #'s M516, J900, W316 and W458.
- UL to UL 263, design #'s K917, L588, U383 and V461.
- *NSF to CAN/ULC S102.2.
- *NSF to ASTM E84

*For detailed information, please refer to:

<https://info.nsf.org/certified/plumbing>

Multi-layer Pipe Benefits

Highest chlorine resistance

- Extremely resistant to chlorine in most demanding conditions (hot water domestic continuous recirculation)
- Provides long term protection against chlorine degradation
- Highest chlorine resistance rating

Resists UV rays 6 times longer

- Offers two layers of defense against damaging UV rays
- Rated 180 days compared to standard PEX pipe with 30 days maximum exposure
- Highest UV resistance rating

Versatility

- Use with crimp joining methods
- Increased flexibility versus the competition

August 2025

Orbia's Building and Infrastructure business Wavin is an innovative solutions provider for the global building and infrastructure industry. Backed by more than 60 years of product development experience, Wavin is advancing life around the world by building healthy, sustainable environments for global citizens. Whether it's to improve the distribution of clean drinking water, to make sanitation accessible for everyone, to create climate resilient cities, or to design comfortable living spaces, Wavin collaborates with municipal leaders, engineers, contractors, and installers to help future-proof communities, buildings and homes. Wavin has 12,000+ employees around 65 production sites worldwide, serving over 80 countries through a global sales and distribution network.

Wavin 950 Winter Street, South Entrance 1st Floor, Waltham, MA 02451, United States | 5700 Côte de Liesse Montréal, QC H4T 1B1
Phone CAN 514-735-7585 / 1800-561-1169 | US 514-735-3632 / 1800-763-3632 | E-mail customer.service@orbia.com | wavin.us | wavin.ca

© 2025 Wavin Wavin reserves the right to make alterations without prior notice. Due to continuous product development, changes in technical specifications may change. Installation must comply with the installation instructions.